

Comforser



SPECIFICATIONS

Tire Size	LI/SS	PR	Rim	Tire Dimensions			MAX. Load(kg)		MAX. Load(lbs)		MAX. Press (kPa/lbs)
				O.D	S.W	G.D	Single	Dual	Single	Dual	
31×10.50R15LT	109Q	6PR	8.5	781	268	15.3	1030	—	1875	—	350/51
32×11.50R15LT	113Q	6PR	9.0	807	290	15.3	1150	—	2095	—	350/51
33×12.50R15LT	108Q	6PR	10.0	832	318	15.3	1000	—	2095	—	250/35
LT235/85R16	120/116Q	10PR	6.5	812	235	15.3	1380	1260	850	2780	550/80
LT245/75R16	120/116Q	10PR	7.0	780	248	15.3	1380	1260	2150	2780	550/80
LT265/75R16	119/116Q	8PR	7.5	810	267	15.3	1360	1250	1985	2755	450/65
LT285/75R16	122/119Q	8PR	8.0	840	286	15.3	1500	1360	2270	3000	450/65
LT315/75R16	121Q	8PR	8.5	884	313	15.3	1450	—	2335	—	350/51
LT265/70R17	118/115Q	8PR	8.0	810	272	15.3	1320	1215	2095	2680	450/65
LT285/70R17	121/118Q	8PR	8.5	838	292	15.3	1450	1320	2470	2910	450/65
LT305/70R16	118/115Q	8PR	9.0	840	311	15.3	1320	1215	1985	2680	350/51