



KF550

- **Silica compound** ---- With latest silica compound technology tread compound yields excellent wet and dry.
- **Ride & Noise** ---- Improved stopping distance, superior acceleration performance and reduced pattern noise are provided by the firm central rib and long central interlock button.
- **Hydroplaning** ---- The optimal design with enlarged main grooves facilitates water drainage to minimize hydroplaning.
- **Wet & Dry Handling** ---- Side slot continuously connect to the wide circumferential grooves enhance the water drainage at the center of the contact patch and strengthen the controlling power even in wet conditions.

Contact Now

Parameter					
INCH	SIZE	LI/SI	TERAD DEPTH (mm)	STANDARD RIM	UTQG
13	175/70R13	82T	8	5J	320 A A
14	175/65R14	82T	8.3	5J	320 A A
	175/65R14	86T XL	8.3	5J	320 A A
	185/65R14	86H	8.3	5 1/2J	320 A A
	185/60R14	82H	8	5 1/2J	320 A A
15	185/65R15	88H	8	5 1/2J	320 A A
	195/65R15	91V	8.3	6J	320 A A
	195/65R15	95T XL	8.3	6J	320 A A
	205/65R15	94V	8.3	6J	320 A A
	205/65R15	94H	8.3	6J	320 A A
	185/60R15	88H XL	8	5 1/2J	320 A A
	195/60R15	88V	8.3	6J	320 A A
	185/55R15	82V	8	6J	320 A A
	185/55R15	86V XL	8	6J	320 A A
	195/55R15	85V	8	6J	320 A A
	195/50R15	82V	8	6J	320 A A