



WILDCLAW A/T

- **Multi-Praction Traction and Handling**---The tread pattern and ratio is balanced for-road traction and on-road handling Coupling joints beteen tread block elements excessive flex for better traction and steering reponse on and off road.

- **All-Season Performance**---Deep sipes and lateral voids effectively channle away Siping helps resist hydroplaning by cutting through pockest of water on road surfaces This technology provides all-season traction.

- **Off-Road Performance**---The lugs on the shoulder are stggered to improve traction in deep sand and loose dirt.

Parameter

INCH	SIZE	LI/SI	TERAD DEPTH (mm)	STANDARD RIM	UTQG
15	31*10.5R15LT	109S	11.5	8 1/2J	-
	31*10.5R15LT OWL	109S	11.5	8 1/2J	-
	P235/75R15	105S	10.0	6 1/2J	500 A B
	P235/75R15 OWL	105S	10.0	6 1/2J	500 A B
16	LT235/85R16E	120/116S	11.5	6 1/2J	-
	LT235/85R16E OWL	120/116S	11.5	6 1/2J	-
	LT225/75R16E	115/112S	11.5	6J	-
	LT225/75R16E OWL	115/112S	11.5	6J	-
	LT245/75R16E	120/116S	11.5	7J	-
	LT245/75R16E OWL	120/116S	11.5	7J	-
	LT265/75R16E	123/120S	11.5	7 1/2J	-
	LT265/75R16E OWL	123/120S	11.5	7 1/2J	-
	P235/70R16	106S	10.0	7J	500 A B
	P235/70R16 OWL	106S	10.0	7J	500 A B
	P265/70R16	112S	10.0	8J	500 A B
	P265/70R16 OWL	112S	10.0	8J	500 A B
17	P265/70R17	115S	10.0	8J	500 A B
	P265/70R17 OWL	115S	10.0	8J	500 A B
	P245/65R17	107S	10.0	7J	500 A B
	P245/65R17 OWL	107S	10.0	7J	500 A B